

Titaan



TITAAN 2-90



"The internal conveyor belts, the external transport conveyor and the hygienic design are the most characteristic features of the Titaan 2-90."

Standard



PUMP CAPACITY 300 m³/h
MACHINE CYCLE 30-50 sec
CHAMBER DIMENSIONS

840 x 890 x 220 mm

MACHINE DIMENSIONS

1061 x 2420 x 1150 mm

SEAL BARS 2 x 840 mm

WEIGHT 850 kg

VOLTAGE 400V-3-50Hz POWER 7.0-9.0 kW

STANDARD

ADVANCED CONTROL SYSTEM,
SENSOR CONTROL, DOUBLE SEAL/
CUT-OFF SEAL/WIDE SEAL (10 MM),
SOFT AIR, STOP BUTTON FOR PARTIAL
OR FULL CYCLE INTERRUPTION

OPTIONS

LIQUID CONTROL, 1-2 CUT-OFF SEAL, TRANSPORT CONVEYOR (400 X 3000 MM OR 600 X 3000 MM), PREPARATION FOR EXTERNAL PUMP, HEATING ELEMENT FOR VACUUM VALVE

DIPTANK 60/100

Shrink technology protects your food product like a second skin. Combined with a vacuum packing machine, Henkelman's Diptanks offer the perfect possibility of creating optimum packages for an aesthetic presentation of your food product.

MACHINE DIMENSIONS

DT60 770 x 790 x 1320 mm DT100 880 x 1000 x 1320 mm

CHAMBER DIMENSIONS

DT60 500 x 600 x 220 mm DT100 600 x 800 x 220 mm

DIPPING DEPTH 220 mm

CYCLE TIME 3-5 sec
MAXIMAL LOADING

CAPACITY 60 kg

WEIGHT DT60 120 kg DT100 155 kg

VOLTAGE 400V-3-50Hz

POWER DT60 9,0 kW DT100 15.0 kW

STANDARD

DIGITAL TIME CONTROL,

INCLUDING

ISOLATION BALLS AGAINST EVAPORATION

